

AVM311 1.3 MP Vandal-Proof IP Camera



FEATURES

- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- 3-axis mechanism for flexible ceiling and wall-mount installation
- External alarm I/O device connection
- ONVIF standard supported to simplify system integration
- IK08 rated, tamper- and vandal-proof lens cover
- Remote Surveillance
 - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
 - -- Push Video available on your iOS and Android devices when used with Push Video NVR series.

SPECIFICATIONS

■ Network		
Network Compression	H.264 / MPEG4 / MJPEG	
Multiple Video Streaming	4 (H.264, MPEG4, MJPEG)	
(Encode Modes, IPS, Resolution)	+ (11.20+, Wil EO+, Will EO)	
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP,	
	HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP, QoS	
ONVIF Compatible	YES (2.0)	
Frame Rate	30fps	
Number of Online Users	10	
Security	(1)Multiple user access levels with password	
	(2)IP address filtering	
	(3)Digest authentication	
Remote Access	Web browsers or CMS software	
■ Camera		
Image Sensor	1/4" SONY CMOS image sensor	
Video Resolution	SXGA to QQVGA	
Min Illumination	1 Lux / F1.5	
Shutter Speed	1/2 to 1/10,000 sec	
S/N Ratio	More than 48dB (AGC off)	
Lens	f3.8mm / F1.5	
Viewing Angle	62.7° (Diagonal) / 53.7° (Horizontal) / 34.1° (Vertical)	
White Balance	ATW	







SPECIFICATIONS (CONTINUED)

■ Camera	
AGC	Auto
IRIS Mode	AES
POE	YES (IEEE 802.3af)
External Alarm I/O	YES (1 in / 1 out)
2/10/11/01/1/1/0	, , ,
MicroSD Card Slot	YES
Vandal Resistance	IK08
Power Source (±10%)	12V / 1A
Operating Temperature	0°℃~40°ℂ
Current Consumption (±10%)	202.5mA
■ Others	
Mobile Surveillance	iOS & Android mobile devices
Motion Detection	YES
Event Notification	FTP / Email / SMS
3-Axis	YES
RTC (real-time clock)	YES
Digital Pan / Tilt / Zoom	YES
Minimum Web Browsing Requirements	 Intel core i3 or higher, or equivalent AMD 2G RAM AGP graphics card, Direct Draw, 32MB RAM Windows 7, Vista & XP, DirectX 9.0 or later Internet Explorer 7.x or later

^{*}The specifications are subject to change without notice.

DIMENSIONS





^{**} Dimensional tolerance: ± 5mm